

Robot Trolley – DATA SHEET

	RT-1500	RT-2500	RT-2500RS	RT-4500
Weight	20.6 kg	34.9 kg	34.9 kg	34.9 kg
Height	295 mm	295 mm	295 mm	295 mm
Width	440 mm	475 mm	475 mm	475 mm
Length	390 mm	540 mm	540 mm	540 mm
Recommended vertical load	300 kgs	300 kgs	300 kgs	300 kgs
Engine/gear box	2 x DC-planetary gear	4 x DC-planetary gear	4 x DC-planetary gear	4 x DC-planetary gear
Speed, unloaded	Approx. 9 m/min	Approx. 9 m/min	Approx. 14 m/min	Approx. 9 m/min
Speed, loaded	Approx. 7 m/min	Approx. 7 m/min	Approx. 14 m/min	Approx. 7 m/min
Recommended towing capacity	Up to 1,500 kgs	Up to 2,500 kgs	Up to 2,500 kgs	Up to 4,500 kgs
Max. gradient pct.	Max. 10%	Max. 10%	Max. 10%	Max. 10%
Security measure	3 min auto shut off	3 min auto shut off	3 min auto shut off	3 min auto shut off
Battery, electrical rating	14.8V Lithium	14.8V Lithium	25.9V Lithium	25.9V Lithium
Battery, capacity	5,000 mAh	10,000 mAh	11,000 mAh	11,000 mAh
Battery, operation capacity	Approx. 30 min	Approx. 30 min	Approx. 30 min	Approx. 30 min
Battery charger	100 – 240V, 1A, 50/60 Hz	100 – 240V, 2A, 50/60 Hz	100 – 240V, 2A, 50/60 Hz	100 – 240V, 2A, 50/60 Hz
Item No	RT0101	RT0104	RT0105	RT0108
Included in all models:				
Remote control				
Battery charger				
Standard bracket				
Storage bag				
Low tower				